



## 15" High-Speed HMI



- 1024 x 768 Pixel High-Resolution TFT
- Ethernet
- 2 Serial Ports
- Aluminum Enclosure

<b>System</b>	<b>CPU</b>	32-bit RISC Cortex-A8, 1 GHz
	<b>Memory (RAM)</b>	256 MB
	<b>Memory (Flash)</b>	256 MB
	<b>RTC</b>	Built-in
<b>I/O Ports</b>	<b>Serial</b>	1 x DE9P COM1: RS-232 1 x DE9S COM1: RS-485 2 or 4 wire, COM3: RS-485 2 wire
	<b>Ethernet</b>	1 x 10/100 Base-T
	<b>CANbus</b>	N/A
	<b>USB Host</b>	1 x USB 2.0
	<b>USB Client</b>	1 x USB 2.0
	<b>Audio</b>	N/A
	<b>Video</b>	N/A
	<b>Wi-Fi</b>	N/A
	<b>HDMI</b>	N/A
	<b>SD Card Slot</b>	SD/SDHC
<b>Display</b>	<b>Display Type</b>	15" TFT LCD
	<b>Size (W x H)</b>	12.04 x 9.06 inches [306 x 230 mm]
	<b>Resolution (pixels)</b>	1024 x 768
	<b>Luminance (cd/m<sup>2</sup>)</b>	400
	<b>Contrast Ratio</b>	700:1
	<b>Max. Colors</b>	16.2 M
	<b>Backlight Lifetime (hours)</b>	50,000+
<b>Touch Screen</b>	<b>Type</b>	4-wire resistive touch
	<b>Active Area Accuracy</b>	Length (X) ± 2%, width (Y) ± 2%
<b>Electrical</b>	<b>Input Voltage</b>	24 ± 20% VDC
	<b>Input Current</b>	1000 mA @ 24 VDC
	<b>Power Isolation</b>	Built-in
	<b>Isolation Resistance</b>	Exceed 50 MΩ at 500 VDC
<b>Mechanical</b>	<b>Enclosure</b>	Aluminum, charcoal grey
	<b>PCB Coating</b>	Yes
	<b>Dimensions (W x H x D)</b>	14.41 x 11.54 x 2.24 inches [366 x 293 x 57 mm]
	<b>Weight</b>	6.06 lbs. [2.75 kg]
<b>Environmental</b>	<b>Mounting</b>	Panel or VESA 75 x 75 mm mounting
	<b>Operating Temperature</b>	32° ~ 122° F (0° ~ 50° C)
	<b>Storage Temperature</b>	-4° ~ 140° F (-20° ~ 60° C)
	<b>Relative Humidity</b>	10% ~ 90% (non-condensing)
	<b>Vibration Endurance</b>	10 to 25 Hz (X, Y, Z direction, 2 G, 30 minutes)
	<b>Ratings</b>	IP65 compliant front panel, NEMA 4X indoor use only
<b>Certifications</b>	cULus, CE, RoHS	
<b>Software</b>	EZwarePlus (v4.00.01 or later)	
<b>Notes</b>		